现货库存、技术资料、百科信息、热点资讯，精彩尽在鼎好！

TOSHIBA Photocoupler GaAs IRed & Photo−Triac

TLP525G,TLP525G−2,TLP525G−4

Triac Drive

Programmable Controllers

AC−Output Module

Solid State Relay

The TOSHIBA TLP525G, −2 and −4 consist of a photo−triac optically coupled to a gallium arsenide infrared emitting diode.
The TLP525G−2 offers two isolated channels in an eight lead plastic DIP package, while the TLP525G−4 provides four isolated channels in a sixteen lead plastic DIP package.

- Peak off−stage voltage: 400V (min.)
- Trigger LED current: 10mA (max.)
- Peak on−stage current: 2Apk (max.)
- Isolation voltage: 2500V_{rms} (min.)
- UL recognized: File no.E67349

Pin Configurations (top view)


TLP525G
TLP525G-2
TLP525G-4
1 : ANODE
2 : CATHODE
3 : TERMINAL 1
4 : TERMINAL 2
1, 3 : ANODE
2, 4 : CATHODE
5, 7 : TERMINAL 1
6, 8 : TERMINAL 2
1, 3, 5, 7 : ANODE
2, 4, 6, 8 : CATHODE
9, 11, 13, 15 : TERMINAL 1
10, 12, 14, 16 : TERMINAL 2

Unit in mm



TOSHIBA 11−5B2

Weight: 0.26g



TOSHIBA 11−10C4

Weight: 0.54g



TOSHIBA 11−20A3

Weight: 1.1g

Absolute Maximum Ratings (Ta = 25°C)

Characteristic			Symbol	Rating		Unit
				TLP525G	TLP525G−2 TLP525G−4	
LED	Forward current		I_F	50	50	mA
	Forward current derating		I_F / °C	−0.7 (Ta ≥ 53°C)	−0.5 (Ta ≥ 25°C)	mA / °C
	Pulse forward current		I_{FP}	1 (100μs pulse, 100pps)		A
	Reverse voltage		V_R	5		V
	Junction temperature		T_j	125		°C
Detector	Off−state output terminal voltage		V_{DRM}	400		V
	On−state RMS current	Ta = 25°C	$I_{T\ (RMS)}$	100	80	mA
		Ta = 70°C		50	40	
	On−state current derating (Ta≥25°C)		I_T / °C	−1.1	−0.9	mA / °C
	Peak on state current		I_{TP}	2 (100μs pulse, 120pps)		A
	Peak nonrepetitive surge current (P_W = 10ms, DC = 10%)		I_{TSM}	1.2		A
	Junction temperature		T_j	115		°C
Storage temperature range			T_{stg}	−55~125		°C
Operating temperature range			T_{opr}	−40~100		°C
Lead soldering temperature			T_{sol}	260 (10s)		°C
Isolation voltage		(Note)	BV_S	2500 (AC, 1min., R.H. ≤ 60%)		V_{rms}

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings.
Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook (“Handling Precautions”/“Derating Concept and Methods”) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Note: Device considered a two terminal device: LED side pins shorted together and detector side pins shorted together.

Recommended Operating Conditions

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Supply voltage	V_{AC}	—	—	120	Vac
Forward current	I_F	15	20	25	mA
Peak on−state current	I_{TP}	—	—	1	A
Operating temperature	T_{opr}	−25	—	85	°C

Note: Recommended operating conditions are given as a design guideline to obtain expected performance of the device. Additionally, each item is an independent guideline respectively. In developing designs using this product, please confirm specified characteristics shown in this document.

Individual Electrical Characteristics (Ta = 25°C)

	Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
LED	Forward voltage	V_F	I_F = 10mA	1.0	1.15	1.3	V
	Reverse current	I_R	V_R = 5V	—	—	10	μA
	Capacitance	C_T	V = 0, f = 1MHz	—	30	—	pF
Detector	Peak off−state current	I_{DRM}	V_{DRM} = 400V	—	10	100	nA
	Peak on−state voltage	V_{TM}	I_{TM} = 100mA	—	1.7	3.0	V
	Holding current	I_H	—	—	0.2	—	mA
	Critical rate of rise of off−state voltage	dv / dt	V_{in} = 120V_{rms}, Ta = 85°C (Figure 1)	200	500	—	V / μs
	Critical rate of rise of commutating voltage	dv / dt (c)	V_{in} = 30V_{rms}, I_T = 15mA (Figure 1)	—	0.2	—	V / μs

Coupled Electrical Characteristics (Ta = 25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Trigger LED current	I_{FT}	V_T = 3V	—	5	10	mA
Capacitance input to output	C_S	V_S = 0, f = 1MHz	—	0.8	—	pF
Isolation resistance	R_S	V_S = 500V, R.H. ≤ 60%	5×10^{10}	10^{14}	—	Ω
Isolation voltage	BV_S	AC, 1 minute	2500	—	—	Vrms
		AC, 1 second, in oil	—	5000	—	
		DC, 1 minute, in oil	—	5000	—	Vdc

Fig.1 dv / dt Test Circuit



I_F – Ta



$I_{T\,(RMS)}$ – Ta



I_{FP} – D_R



I_F – V_F



$\Delta V_F / \Delta Ta$ – I_F



I_{FP} – V_{FP}



NORMALIZED I_{FT} − Ta



NORMALIZED I_H − Ta



NORMALIZED I_{DRM} − Ta



NORMALIZED V_{DRM} − Ta



NORMALIZED LED CURRENT − LED CURRENT PULSE WIDTH



RESTRICTIONS ON PRODUCT USE

20070701-EN

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
  In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the “Handling Guide for Semiconductor Devices,” or “TOSHIBA Semiconductor Reliability Handbook” etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.).These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury (“Unintended Usage”). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in his document shall be made at the customer’s own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patents or other rights of TOSHIBA or the third parties.
- GaAs(Gallium Arsenide) is used in this product. The dust or vapor is harmful to the human body. Do not break, cut, crush or dissolve chemically.
- Please contact your sales representative for product-by-product details in this document regarding RoHS compatibility. Please use these products in this document in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses occurring as a result of noncompliance with applicable laws and regulations.